



Manufacturer & Exporter of:
Tube Tools, Tube Cleaners, Tube Expander, Flexible Shafts
Pipe Beveling Machines, Impact Sockets,
Hydraulic Torque Wrench, High Pressure Water Jet Cleaner.

AIR/HYDRAULIC STUB PULLER

BHÂRTIYÂ

FEATURES:

Improved productivity and better control through foot pedal. Extremely compact, durable, lightweight and portable

package - useful in confined areas. Makes pulling tubes faster and easier.

Quick and easy arrangement to reduce downtime.

Lowest priced system available.

Safe - Totally air operated for use in explosive environments.

Air - Powered Hydraulic Stub Puller set consists of:

- **★** Self Tapping Spear.
- **★** Air Powered hydrulic Pump with FRL unit.
- **★** Stub Puller cylinder assembly (supplied in 2 models).
- * Carrying case.



Model	BAHSP - 4	BAHSP - 9	
Extraction Load (Ton)	4	9	
Overall Dimension (mm) L x	550 x Ø 65.0	550 x Ø 104.0	
Stroke (mm)	150	150	
Recommended Tube Sizes	Up to 3/4" OD	Up to 1.1/4" OD	
Pulling Speed secs. / Stroke	15	30	
Weight (kg) with accessories	9	18.5	

PULLING SPEARS:



Model	Tube O.D. inch	Tube thk. bwg	Model	Tube O.D. inch	Tube thk. bwg
BSS - 0916	3/8	16 - 17	BSS - 2212	7/8	12 -13
BSS - 0918	3/8	18 - 19	BSS - 2214	7/8	14 -15
BSS - 0920	3/8	20 - 21	BSS - 2216	7/8	16 -17
BSS - 0922	3/8	22 - 23	BSS - 2218	7/8	18 - 19
BSS - 1214	1/2	14 - 15	BSS - 2220	7/8	20 - 21
BSS - 1216	1/2	16 - 17	BSS - 2509	1	9 - 10
BSS - 1218	1/2	18 - 19	BSS - 2510	1	10 - 11
BSS - 1220	1/2	20 - 21	BSS - 2512	1	12 - 13
BSS - 1222	1/2	22 - 23	BSS - 2514	1	14 - 15
BSS - 1512	5/8	12 - 13	BSS - 2516	1	16 - 17
BSS - 1514	5/8	14 - 15	BSS - 2518	1	18 - 19
BSS - 1518	5/8	18 - 19	BSS - 2520	1	20 - 21
BSS - 1520	5/8	20 - 21	BSS - 3112	1.1/4	12 - 13
BSS - 1911	3/4	11 - 12	BSS - 3114	1.1/4	14 - 15
BSS - 1912	3/4	12 - 13	BSS - 3116	1.1/4	16 - 17
BSS - 1914	3/4	14 - 15	BSS - 3118	1.1/4	18 - 19
BSS - 1916	3/4	16 - 17	BSS - 3120	1.1/4	20 - 21
BSS - 1918	3/4	18 - 19	-	-	-
BSS - 1920	3/4				



AIR/HYDRAULIC PUMP-MODEL NO. BASP-1008

Length (mm)	264
Width (mm)	135
Height (mm)	205
Weight without oil (kg)	6.6
Hose Length (ft.)	6
Hose I.D. (Inch)	1/4"
Air inlet Port	1/2" BSP
Hydraulic Port	3/8" NPT
Hydraulic Oil	VG ISO 68 Grade
Workinh Air pressure (bar)	7
Working hydraulic pressure (bar)	700

SPRING BALANCER:



Model	Balancing Capacity	Suitable For
SEW - 9	5 - 9 Kgs	BAHSP - 4
SEW - 22	15 - 22 Kgs	BAHSP - 9